

ENCOTEC 10X ADHESIVE

Description:

Encotec 10X is a versatile adhesive designed for commercial spray applications of cellulose, rockwool and fiberglass. Its exceptional bonding properties make it highly compatible for spray application of insulation to wood, concrete and metal buildings. Encotec 10X dries to a tough, flexible, water resistant film, creating a highly bonded and durable finish.

Application:

For use in new construction and retrofit applications:

- Warehouses
- Manufacturing Facilities
- Parking Garages
- Restaurants
- Hospitals
- Offices
- Bars/Lounges
- Farm/Livestock Buildings

Preparation:

Surface must be free of dust, oil, grease, silicone coatings, etc. It is recommended that metal surfaces be primed with Encotec Primer/Sealer.

Water Dilution Ratio:	<u>Application</u>	<u>1"</u>	<u>2"</u>	<u>3"</u>	<u>4"</u>	<u>Overcoat</u>
	Ceiling	6 to 1	5 to 1	4 to 1	n/a	2 to 1
	Wall	6 to 1	5 to 1	5 to 1	5 to 1	2 to 1

Note: These water-to-adhesive dilution ratios are for cellulose insulation and may vary depending on thickness, substrate conditions, vertical or horizontal spray, and other related conditions. Other insulation types may require different dilution ratios. Stir well before and after diluting and prior to using.

Physical Properties:

Type: Formulated Resin Terpolymer
Appearance: White Fluid – Dries Clear
Viscosity: Approx. 400 cps
Flammability: Non-flammable
Corrosiveness: Non-corrosive

Form: Emulsion
pH: 5.0-6.5
Wt./Gal.: 8.85 lb.
Odor: Nil
Solids: 40% ± 2%

Packaging:

Plastic Pails and Metal Drums

Shelf Life:

Six (6) months. Store at room temperature. Keep from freezing.

