

Fiberlite Technologies, Inc.

3605 E. 25th Street
Joplin, MO 64804-3224
800-641-4296
www.fiberlitetech.com

* * * Product Data * * *

ENCOTEC 10X ADHESIVE

Description: Encotec 10X is a versatile adhesive designed for commercial spray application of cellulose, rockwool and fiberglass to a variety of surfaces. Its exceptional bonding properties makes it highly compatible for spray application of insulation to wood, concrete and metal buildings. The bonding of insulation to other substrates such as; vinyl, foil and paper facings, and glass surfaces may also be attained. Encotec 10X Adhesive dries to a tough, flexible, water resistant film creating a highly bonded and durable finish to many substrates.

<u>Water Dilution Ratio:</u>	Cellulose	6 to 1
	Rockwool & Fiberglass	5 to 1

Note: Dilution ratios may vary depending on thickness, substrate conditions, vertical or horizontal spray, and other job related conditions. Stir well before and after diluting and prior to using.

Preparation: Surfaces must be free of dust, oil, grease, silicone coatings, etc. It is recommended that contaminated metal surfaces be cleaned with Encotec Etcher/Cleaner.

Packaging: Plastic Pails and Metal Drums.

Storage Life: Six (6) months. Store at room temperature. Keep from freezing. (Non-flammable/Non-corrosive).

FDA Status: Approved.

Physical Properties:

Form:	Emulsion	Solids: 40%±2%
Type:	Formulated Resin Terpolymer	pH: 5.0-6.5
Appearance:	White Fluid - Dries Clear	Wt./Gal.: 8.85 lbs.
Viscosity:	Approx. 400 CPS	Odor: Nil

This information is accurate and reliable to the best of our knowledge and will vary with manufacturing and testing tolerances. We have no control over installation workmanship, accessory materials or application conditions, and make no representation or expressed or implied warranty, either as to merchantability or fitness, beyond the description herein.

“WHERE INSULATION, ADHESIVES & TECHNOLOGY COME TOGETHER”