

Fiberlite Technologies, Inc.

3605 E. 25th Street
Joplin, MO 64804-3224
800-641-4296
www.fiberlitetech.com

* * * Product Data Sheet * * *

ENCOTEC 52X ADHESIVE

Description: Encotec 52X is a unique, high bonding, adhesive designed for commercial spray application of insulation to a wide range of surfaces. Its properties include:

- *Excellent adhesion to metals and plastic (polymeric) surfaces.
- *Tough, flexible film.
- *Water, oil and grease resistance.
- *Acid and alkali resistance.
- *UV and ozone resistance.
- *Dries clear and odorless.
- *Wide temperature range adhesion cold and hot.
- *FDA approved.

<u>Water Dilution Ratio:</u>	Cellulose	8 to 1
	Rockwool & Fiberglass	7 to 1

Note: Dilution ratios may vary depending on thickness, substrate conditions, vertical or horizontal spray, and other job related conditions. Stir well before and after diluting and prior to using.

Packaging: Plastic Pails and Metal Drums.

Storage Life: Six (6) months. Store at room temperature. Keep from freezing. (Non-flammable/Non-corrosive).

FDA Status: Approved.

Physical Properties:

Form:	Emulsion	Solids: 55%±1%
Type:	Formulated Resin Copolymer	pH: 4.0-5.0
Appearance:	White Fluid - Dries Clear	Wt./Gal.: 8.85 lbs.
Viscosity:	Approx. 3,100-4,400 CPS±200 CPS	Odor: Nil

This information is accurate and reliable to the best of our knowledge and will vary with manufacturing and testing tolerances. We have no control over installation workmanship, accessory materials or application conditions, and make no representation or expressed or implied warranty, either as to merchantability or fitness, beyond the description herein.

“WHERE INSULATION, ADHESIVES & TECHNOLOGY COME TOGETHER”