

ENCOTEC PRIMER/SEALER

Description: Encotec Primer/Sealer is an effective liquid sealer designed to be sprayed onto metal and concrete surfaces prior to the application of the “SATAC” System. The primer allows Encotec Adhesives to form a bond to the structure.

Preparation: Surface should be clean, dry and at a temperature above 50° and below 120°

Application:

Recommended Solvent:	Water
Conventional Spray:	Up to 10% Reduction Max.
Airless Spray:	Up to 10% Reduction Max.
Clean Up:	Water
Drying Conditions @ 72°	Tack Free <45 Minutes
	Dry time depends on temperature, humidity and film thickness

Coverage: Approx. 700 board feet per gallon using an airless paint sprayer and a spackle application method.

Characteristics:

Gloss:	10% @ 60°	Weight/Gallon:	7.3 lbs.
System:	Acrylic Latex	Actual VOC:	0.207 lbs./gal.
Pigment:	Calcium Carbonate	HAPS:	0.00 lbs./gal
Weight Solids:	52%	Viscosity:	100 KU
Volume Solids:	36%		

Packaging: Plastic Pails (5 gal.)

Storage and Handling:

Shelf Life:	2 Years
Storage:	Do not store in direct sunlight
	Do not store above 120°F
	Do not freeze

