

Fiberlite Technologies, Inc.

3605 E 25th Street
Joplin, MO 64804-3224
800-641-4296
www.fiberlitetech.com

* * * Product Data * * *

ENCOTEC QUIK-DRY

Description: Encotec Quik-Dry accelerates drying time of wall cavity sprayed insulation; utilizing Quik-Dry may reduce the drying time of sprayed insulation in the stud cavity by as much as one third.

Encotec Quik-Dry works as a surfactant to capture water molecules and increases the evaporation rate. This product is biodegradable, non-flammable and non-toxic and is recommended when environmental conditions extend the drying time of wall cavity applications.

Water Dilution Ratio: One (1) quart per 55 gallons of water.

Note: Dilution ratios may vary depending on thickness, substrate conditions, vertical or horizontal spray, and other job related conditions. Stir well before and after diluting and prior to using.

Packaging: Five (5) gallon plastic pail.

Storage Life: Six (6) months. Store at room temperature. Note: If product freezes, it will reconstitute without loss of efficiency when returned to room temperature and agitated.

Physical Properties:

| | |
|--|-------------------------------------|
| Boiling Point: 212°F | Appearance: Blue Liquid |
| Vapor Pressure: of water (11mmHg) | Solubility in Water: Soluble |
| Specific Gravity: 1.08 (H ₂ O) =1 | Weight per Gallon: 8.34 lbs./gallon |
| % Solids by Wgt: 0% | PH: 7.9 Odors: Slightly Sweet |
| Evaporation Rate: 1.0 (butyl acetate =1) | Freezing Point: 32°F |

This information is accurate and reliable to the best of our knowledge and will vary with manufacturing and testing tolerances. We have no control over installation workmanship, accessory materials or application conditions, and make no representation or expressed or implied warranty, either as to merchantability or fitness, beyond the description herein.

“WHERE INSULATION, ADHESIVES & TECHNOLOGY COME TOGETHER”

